

PLATING ON EXTERIOR OF SLEEVE ONLY.
FLASH ON INTERIOR OF SLEEVE ACCEPTABLE.

* - LENGTH L IN 1/16 INCH INCREMENTS ±.010 (2 DIGITS)
LENGTH L IN THOUSANDTHS OF AN INCH ±.005 (3 OR 4 DIGITS)

DIMENSION DATA (ALL DIMENSIONS BEFORE PLATING)

SIZE CODE	BOLT SIZE	A ±.005	DI DIA	DO DIA	L MAX	(HF)	(HS)
06	.1900	.300	.1880-.1895	.2200-.2210	1.000	.047	.054
08	.2500	.393	.2480-.2495	.2802-.2812	1.125	.061	.068
10	.3125	.472	.3105-.3120	.3427-.3437	1.187	.067	.075
12	.3750	.558	.3730-.3745	.4052-.4062	1.250	.077	.085
14	.4375	.670	.4355-.4370	.4677-.4687	1.375	.098	.106
16	.5000	.759	.4980-.4995	.5302-.5312	1.500	.109	.117

MATERIAL AND FINISH DATA

CODE	MATERIAL	SPEC.	CONDITION	PASSIVATE
C	A-286 CRES	AMS 5525	AS FORMED	AMS 2700
D	A-286 CRES	AMS 5525	ANNEALED	AMS 2700

SURFACE FINISH


CODE	TREATMENT	SPEC.
N	NONE	
A	IVD ALUMINUM	MIL-DTL-83488
C	CAD PLATED	AMS-QQ-P-416 TYPE I CLASS 2

LUBRICATION DATA

CODE	LUBRICATION	SPEC.
NONE	NONE	
B	NONE	
L	CETYL ALCOHOL	MIL-L-87132

EXAMPLE PART NUMBER

JK5542 C 08 N 200 L



UNLESS OTHERWISE SPECIFIED, ALL DIMENSIONS ARE IN INCHES AND TOLERANCES ARE AS SHOWN BELOW. DIMENSIONAL TOLERANCES AND SYMBOLS PER ANSI Y14.5M-1982.

PROPRIETARY PARTS SHOWN IN THIS DRAWING ARE THE SUBJECT OF ISSUED UNITED STATES AND FOREIGN PATENTS AND PATENTS PENDING. UNAUTHORIZED REPRODUCTION AND/OR DISTRIBUTION OF THIS DRAWING IS SPECIFICALLY PROHIBITED.

GLICK BOND

CARSON CITY
NEVADA 89706

HOLEMOD

APPROVALS	DATE
DRAWN <i>DAC</i>	6APR05
CHECKED <i>DAC</i>	8MAR19
RELEASED <i>B Khodnegah</i>	9MAR19
REVISED <i>DAC</i>	8MAR19

TITLE			
SLEEVE, BOLT FIT, 100° SHEAR HEAD			
SIZE	CAGE CODE	DWG. NO.	REV.
A	66530	JK5542	8
SCALE	4/1	8MAR19	SHEET 1 OF 1